## PORSCHE GT3 CUP CAR (2004-PRESENT) PASSENGER SIDE SHOULDER HARNESS MOUNT BAR INSTALLATION INSTRUCTIONS

The R-1040 Harness Mount Bar has been designed and tested to provide a mounting point for the shoulder harness portion of a multipoint harness the Passenger Side in a Porsche GT3 Cup Car (2004-2012).

Note: Brey-Krause suggests the install of the R-1040 GT3 Cup Car Passenger Harness Mount Bar to be completed by a professional.

Step 1: Position the R-1040 at the appropriate height in relation to the shoulder slots of the passenger seat being installed. The treaded ends allow extending either side up to 5/8<sup>th</sup> inch.

Step 2: Have both bar mount sides of the clamps loosely installed on the bar ends. First loosely install the outboard clamp on the cage tube. Then position and loosely install the inboard clamp to the opposite cage tube (where the driver side harness bar is welded).

Step 3: Tighten clamps with the bar tightly wedged and level between the cage tubes. Bar should be orientated as shown below (height of bar may vary).





Step 4: Reference belt harnesses manufacturer's installation instructions for mounted the shoulder harnesses to the R-1040. It is common practice to cross shoulder belts to prevent slippage.

Performance driving events are by nature potentially hazardous to your health. Brey-Krause Mfg. Co. Inc. shall not be liable for injury, consequential, or other types of damages resulting from the use or misuse of our products. Proper installation of these parts is critical and should only be done by a professional shop.