

Front Brake Upgrade Kit



PRODUCT CONTENTS (PLEASE DOUBLE CHECK CONTENTS)

- 4-piston calipers
- High performance brake pads
- Brake rotors

The following part numbers reference individual parts or sets:

- 4-piston calipers + pads: BXBS-10500
- 4-piston calipers, set: BXBS-10100
- High performance pads: BXBS-100100
- Brake rotors, set: BXBS-10200
- 4-piston caliper, single: BXBS-10050
- Brake rotors, left: BXBS-10150-L
- Brake rotors, right: BXBS-10150-R

INSTALLATION OF THIS PRODUCT SHOULD BE PERFORMED BY A TRAINED PROFESSIONAL OR EXPERIENCED MECHANIC TO ENSURE PROPER OPERATION AND FUNCTION OF THE BRAKE SYSTEM. ALWAYS USE SAFETY PRECAUTIONS AND CORRECT AUTOMOTIVE TOOLS.



Step 1: Disassemble the brake system by removing the calipers and lines. It is recommended that the lines be replaced with new or steel braided hoses.



Step 2: Disassemble and remove the brake rotors. Remove any material from the hub faces. Clean the areas with brake cleaner or degreaser.



Step 3: Place the new BLOX Racing front rotor on to hub, making sure it sits and fits flush against the axle hub. Make sure rotor slots are facing correct direction.



Step 4: Mount the new BLOX Racing front caliper. Use “red” Loctite® 271 on the bolt threads. Torque to 60 ft/lbs.



Step 5: Slide the new BLOX Racing brake pads into place. Make certain that the friction material is facing the rotor. Install the brake pad retainer clip. Connect brake hose.

Double-check brake line clearance by turning steering wheel lock-to-lock and making sure clearance is provided for suspension travel and movement.

Bleed brakes according to OEM instructions and recommendations. Always test brake pedal pressure and check for leaks. Repeat steps for opposite side.

