PERFORMANCE BY





INSTALLATION GUIDE

iE Catback Exhaust System For VW MK8 GTI IEEXDB3



This installation guide is for instructional purposes only. For best results, professional installation by an experienced technician is always recommended. By reading this guide you agree Integrated Engineering is not responsible for any damage or personal injury caused by incorrect installation.

DIFFICULTY



Expect 1.5 hours on average

REQUIRED PARTS

• No additional parts are required for this install

REQUIRED TOOLS

- Exhaust clamp removal tool or Pry Bar
- 10, 12, 13, 14, 15mm socket
- Ratchet and extension

OPTIONAL PARTS

- iE Performance Downpipe for MK8 GTI (IEEXDB5)
- iE Optional Resonator (IEEXDB3-1)

BEFORE YOU BEGIN

It is highly recommended to pre-read this entire guide ahead of your installation to familiarize yourself with each step. Always park your vehicle in a safe and level location and allow plenty of time for the engine bay and exhaust to completely cool. Locate and prepare your work space with each required tool listed above. Unbox all components and verify the contents and quantities before you begin. If anything is missing or damaged, please contact us for immediate help at support@performancebyie.com

SPECIAL NOTE:

This install guide has been photographed and written on a 2024 VW GTI. Some steps and factory hardware specifications may vary depending on vehicle model, year, and region. This guide is for refrence purposes only. If you are unsure of the installation procedure for any individual step or part, please seek professional help before proceeding.




INCLUDED PARTS

- 01 Exhaust Reducer Kit w/Clamps, 76mm x 65mm
- 02 66MM Band Clamp for Exh Tips (2x)
- 03 MK8 GTI Exhaust Rear Section
- 04 MK8 GTI Muffler Delete Section
- 05 2.5" Single Wall Exhaust Tip (2x)
- 06 MK8 GTI Exhaust Resonator Section
- 07 3" BUTT EXHAUST BAND CLAMP (2x)
- 08 Black-Oxide Steel Oversized Washer for M10 Screw Size, 10.5 mm ID, 19 mm 0D (4x)

Some items may be partially assembled.






Remove two 10mm plastic nuts on cross beam cover.








Remove four 13mm nuts to remove the cross bar.


4



Loosen two 13mm nuts to remove exhaust clamp








Remove two exhaust hanger bolts (one on each side) using 13mm socket. Take note that these are the final bolts holding the exhaust up, so be ready for it to drop. Ideally it's good to have another pair of hands ready to pull the exhaust.





Remove the exhaust from the vehicle.

8



Install the front exhaust clamp and hand tighten using 13 and 14mm drivers. You will tighten to spec at the end so leave them loose enough that they can be adjusted. If you are bolting your catback up to an OE downpipe, you will use the reducer as seen above. If you have an aftermarket downpipe and have purchased the IEEXDB3-1 optional resonator, you will install it in place of this front section.







Transfer your OE hangers to your IE catback.



Raise middle section into place and install exhaust clamp and hanger in place.










Raise the rear section into place and install the exhaust clamp and the two rear hangers.



Install tips using a 12mm driver and adjust them to the desired fit with the rear bumper.






your way from the front to the back and tighten all clamps down to 42 ft/lbs. This may take a couple passes to ensure fitment is perfect. Reinstall cross beam and other OE fasteners.

Installation is now complete! Enjoy the look, sound, and performance of your new iE Catback System!



Thank you for purchasing an Integrated Engineering product. We are dedicated to serving your performance needs. Please check our website frequently for new product releases. If you have any questions or concerns about this product please do not hesitate to contact us.



HOW WAS YOUR INSTALL?





Awesome! Please leave a review. share.performancebyie.com



Sorry, let us make it right. support.performancebyie.com



801.484.2021

WWW.PERFORMANCEBYIE.COM

SUPPORT@PERFORMANCEBYIE.COM



Brother owned since 2007. Garage started for beer money.

