





HARDWARE: 1- Y-STRAP

2- SPACERS 4-M10 HEX BOLTS » RATCHET

**TOOLS REQUIRED** 

- » 15MM SOCKET
- » TORQUE WRENCH

## Spare Tire Mount Instructions (P141U300)



First back the 4 bolts out of the Rear Mounting location. (Rear Mounting location is inside the cargo area)



Set spare tire mount in place and align the 4 holes. Replace the 4 bolts you removed in step #1.



Now that the spare tire mount is secure place spare tire on top.



If your version of cage has the spacer indentation on the rear bungs (Illustrated above left), apply the provided spacers.\* If no spacer is required proceed to step 3.\*



Tighten the 4 bolts and then torque to 40ft.lb.



Using the Y strap provided secure the spare tire to the spare tire mount.
Now go enjoy another adventure!

## **WARNING**

- **Never** stick hands, head or arms outside of vehicle at any time when it is in motion.
- Always wear and use proper safety equipment when using any Pro Armor product.
- Improper use of directions and/or product can result in injury to yourself or damage to your vehicle.
- Disclaimer please read: This product is sold without warranty expressed or implied. No warranty or representation is made as to the products ability to protect the user / occupant from any injury or death in any manner of use. The user assumes that risk. The effectiveness of this equipment is directly related to the manner in which it is installed, used, and / or maintained.

Proper installation is solely the responsibility of the installer, and will not be assumed by Pro Armor.

If you have questions about your installation or are unable able to complete installation, contact Pro Armor Customer Service (888)312-7667 or have an authorized dealer or trained technician, inspect your installation.