



WEB LINK: http://lodoffroad.com/assets/pdfs/JRB9620 YJ TJ LJ EXPEDITION REAR BUMPER.pdf

VERIFY YOU HAVE ALL THE COMPONENTS BEFORE STARTING THE INSTALLATION. REFER TO THE ENGINEERING DRAWINGS AT THE END OF THIS DOCUMENT FOR A COMPLETE PARTS LIST



Start by removing your rear bumper. You will need to drill two mounting holes on each side in the rear cross member. This step is only needed on 1998 and newer TJ's. Earlier TJ's and YJ's already have these holes in place.


Follow the diagram shown for drilling 1/2" diamater mounting holes 7-13/16" from the outside mounting holes.



To improve your drilling accuracy it is a good idea to start small bit and get progressively larger or use a step drill. Be careful when you punch thru as to not hit the gas tank behind the cross member.

Next lower the gas tank skid plate by removing the 4 screws shown below. This will allow the skid plate to drop a few inches to gain access behind the rear cross member.






Use a floor jack or a helper to hold the rear bumper up to the rear cross member.




Install the 7/16" Hex Bolts, Nuts and Washers into the two outside mounting holes first. Leave these slightly loose while you finish the bumper installation



Install the Bottom Bracket as shown using 3/8" Hex Bolt and washers into the bumper, and the supplied metric M12 Hex bolt into the frame.

Note some older Jeeps may have a different threaded nut in frame. Be sure to check the thread before tightening. Do not force the bolt into the thread if you are not sure.

Once all the bolts are installed, make sure the bumper is centered on the Jeep and level side to side. Tighten all the mounting bolts securely. Once the bumper is secure reinstall the gas tank skid plate.




Maintenance

Rear Bumper:


- Periodically check and re-tighten all fasteners.
- Periodically check your Bumper for scratches, dings, or rust spots which can happen over time or after heavy use. It is important to address these areas as soon as possible to prevent rust and corrosion from spreading. We recommend using Rustoleum[©] brand Black Semi-Gloss Protective Enamel (oil based). Apply using a foam brush by dabbing to match the powder coat texture.









On:









PACKAGED SEPERATE IF BUMPER IS BARE STEEL


LOD LOGO (x1)





YJ/TJ/LJ Jeep
EXPEDITION Series
REAR BUMPER
Hardware Kit
Sheet 1
Packaged by:

















FLAT WASHER Ø3/8" X 1.00" (0159679)

(x16)

