

INSTALLATION GUIDE

MK7 GTI CATBACK EXHAUST



TOOLS REQUIRED:

13mm socket
Ratchet
10mm socket

WHAT'S IN THE BOX:

1x MAPerformance MK7 GTI Front Section
1x MAPerformance MK7 GTI Muffler Section
1x MAPerformance MK7 GTI Tip Section
2x 3" Vband Clamp
2x Tips w/Clamps
1x Slip Clamp (OE Downpipe Fitment)
1x 3" Vband Clamp (MAP Downpipe)

1. REMOVE BOTH FRONT AND REAR UNDER CHASSIS BRACKETS (BOTH HAVE 4 13MM NUTS)

2. LOOSEN SLIP CLAMP HOLDING DOWNPIPE AND CATBACK TOGETHER

3. REMOVE CENTER EXHAUST HANGER BY REMOVING THE ONE 13MM NUT

4. REMOVE MUFFLER SECTION EXHAUST HANGERS BY REMOVING ALL 13MM NUTS

**5. LOWER EXHAUST OFF THE CAR
REMOVE EXHAUST HANGERS FROM THE STOCK EXHAUST**

**6. INSTALL THE EXHAUST HANGERS ONTO THE
MAP CATBACK**

**NOTE: WE INCLUDE ONE EXHAUST HANGER BECAUSE THE GTI HAS AN EXTRA UNUSED HANGER.
INSTALL THE INCLUDED RUBBER HANGER ON THE POST MUFFLER HANGER ON THE NEW EXHAUST.**



**7. INSTALL THE REAR Y PIPE ONTO THE CAR
SECURE WITH 4 NUTS YOU REMOVED PREVIOUSLY**

**8. INSTALL THE RESONATED SECTION ONTO THE DOWNPIPE AND BE SURE THE
PIPE IS CLOCKED IN THE CORRECT ORIENTATION (AS PICTURED)**



8. CONTINUED



**9. INSTALL MUFFLER SECTION WITH THE OEM HANGER AND MAP HANGER (AS PICTURED)
CONNECT THE Y PIPE AND THE RESONATED SECTION WITH INCLUDED VBANDS, DO NOT TIGHTEN**



**10. ENSURE ALL PIECES ARE CLOKED
CORRECTLY AND THERE IS PLENTY OF ROOM**

**11. TIGHTEN ALL VBAND CLAMPS STARTING
FROM THE DOWNPIPE TO RESONATED
CONNECTION, THEN RESONATOR TO MUFFLER
SECTION, AND LASTLY MUFFLER TO
Y PIPE SECTION**

**12. INSTALL SLIP ON TIPS, ORIENTAT AS PICTURED
TIGHTEN 10MM CLAMP ONCE POSITION IS AS DESIRED.**



12. CONTINUED

13. START AND CHECK FOR LEAKS

14. REINSTALL UNDER CHASSIS BRACKETS



THANK YOU FOR CHOOSING MAPERFORMANCE!

If you have any problems or concerns during installation of this product, feel free to call or email us:

1-888-MAPERFORMANCE

support@maperformance.com

Show us some photos! @maperformance / #maperformance