

1613M WHEEL SPEC

MAVERICK 1613M **21inch** NORMAL RIM [2pieces]

Size	S-Lo Disk 5H-114.3 5H-120							Lo Disk 5H-112 5H-114.3 5H-120							Hi Disk 5H-112 5H-114.3 5H-120							
	Order Inset	Inset (Rim Depth) mm						Order Inset	Inset (Rim Depth) mm						Order Inset	Inset (Rim Depth) mm						
21×9.0J	55〜24	5(59)	44(65)	38(71)	32(77)	26(83)		48〜17	45(57)	39(63)	33(69)	27(75)	21(81)		32〜1			30(56)	24(62)	18(68)	12(74)	6(80)
21×9.5J	55〜17	5(65)	44(71)	38(77)	32(83)	26(89)	20(95)	50〜10	45(63)	39(69)	33(75)	27(81)	21(87)	15(93)	38〜-7		36(56)	30(62)	24(68)	18(74)	12(80)	6(86)
21×10.0J	55〜18	5(72)	44(78)	38(84)	32(90)	26(96)	20(102)	50〜11	45(70)	39(76)	33(82)	27(88)	21(94)	15(100)	45〜-6	42(57)	36(63)	30(69)	24(75)	18(81)	12(87)	6(93)
21×10.5J	55〜24	5(78)	44(84)	38(90)	32(96)	26(102)		50〜17	45(76)	39(82)	33(88)	27(94)	21(100)		46〜1	42(63)	36(69)	30(75)	24(81)	18(87)	12(93)	6(99)
21×11.0J	55〜24	5(84)	44(90)	38(96)	32(102)	26(108)		50〜17	45(82)	39(88)	33(94)	27(100)	21(106)		46〜1	42(69)	36(75)	30(81)	24(87)	18(93)	12(99)	6(105)

* There is no protrusion of the top surface of the disk from the edge of the rim flange on all sizes.

- DISK FINISH: HYPER METAL BLACK, SAMURAI GOLD, GLAZE BLACK
- COMPONENT PARTS: CENTER CAP (2 colors for Hi type and 6 colors for Lo type are available), AIR VALVE
- *As of November 30, 2023, the long adapter is no longer included.
- RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.
- ※SAME PRICES ON YOUR CUSTOM ORDER.

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)											
	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi									
21 Normal	--	--	--	--	φ66.5	705KG	φ30	φ14.5	φ73	690KG	φ30	φ14.5	φ72.5	815KG	φ30	φ14.5	32	39	55									
20 Reverse	--	--	--	--																								
20 Normal	φ65	540KG	φ30	φ14.5		700KG																						
19 Reverse																												
19 Normal																												
18 Reverse																												

■MAVERICK1613M is compatible with VIA815KG (5H-120). It can be installed on all grades of Alphard/Vellfire (40 series) and Lexus LM (H10 series).

MAVERICK 1613M 20inch REVERSE RIM

[2pieces]

Size	S-Lo Disk 5H-114.3 5H-120							Lo Disk 5H-112 5H-114.3 5H-120							Hi Disk 5H-112 5H-114.3 5H-120							
	Order Inset	Inset (Rim Depth) mm						Order Inset	Inset (Rim Depth) mm						Order Inset	Inset (Rim Depth) mm						
20×8.0J	55～37	53(44)	47(50)	41(56)	37(60)			50～30	48(42)	42(48)	36(54)	30(60)			34～14			33(41)	27(47)	21(53)	15(59)	
20×8.5J	55～30	53(50)	47(56)	41(62)	35(68)	30(73)		50～23	48(48)	42(54)	36(60)	30(66)	24(72)		40～7		39(41)	33(47)	27(53)	21(59)	15(65)	9(71)
20×9.0J	55～22	53(56)	47(62)	41(68)	35(74)	29(80)	23(86)	50～15	48(54)	42(60)	36(66)	30(72)	24(78)	18(84)	46～-1	45(41)	39(47)	33(53)	27(59)	21(65)	15(71)	9(77)
20×9.5J	55～22	53(63)	47(69)	41(75)	35(81)	29(87)	23(93)	50～15	48(61)	42(67)	36(73)	30(79)	24(85)	18(91)	46～-1	45(48)	39(54)	33(60)	27(66)	21(72)	15(78)	9(84)
20×10.0J	55～28	53(69)	47(75)	41(81)	35(87)	29(93)		50～21	48(67)	42(73)	36(79)	30(85)	24(91)		46～5	45(54)	39(60)	33(66)	27(72)	21(78)	15(84)	9(90)
20×10.5J	55～24	53(75)	47(81)	41(87)	35(93)	29(99)		50～17	48(73)	42(79)	36(85)	30(91)	24(97)	18(103)	46～1	45(60)	39(66)	33(72)	27(78)	21(84)	15(90)	9(96)

* There is no protrusion of the top surface of the disk from the edge of the rim flange on all sizes.

- DISK FINISH：HYPER METAL BLACK, SAMURAI GOLD, GLAZE BLACK
- COMPONENT PARTS: CENTER CAP (2 colors for Hi type and 6 colors for Lo type are available), AIR VALVE
- *As of November 30, 2023, the long adapter is no longer included.
- RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.
- ※SAME PRICES ON YOUR CUSTOM ORDER.

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)		
	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi
21 Normal	--	--	--	--	φ66.5	705KG	φ30	φ14.5	φ73	690KG	φ30	φ14.5	φ72.5	815KG	φ30	φ14.5	32	39	55
20 Reverse	--	--	--	--															
20 Normal	φ65	540KG	φ30	φ14.5		700KG													
19 Reverse													--	--	--	--			
19 Normal													--	--	--	--			
18 Reverse													--	--	--	--			

■MAVERICK1613M is compatible with VIA815KG (5H-120). It can be installed on all grades of Alphard/Vellfire (40 series) and Lexus LM (H10 series).

MAVERICK 1613M **20inch** NORMAL RIM

[2pieces]

Size	S-Lo Disk 5H-114.3								Lo Disk 5H-100 5H-112 5H-114.3 5H-120								Hi Disk 5H-114.3							
	Order Inset	Inset (Rim Depth) mm							Order Inset	Inset (Rim Depth) mm							Order Inset	Inset (Rim Depth) mm						
20×8.5J	46～24		44(59)	38(65)	32(71)	26(77)			39～17		39(57)	33(63)	27(69)	21(75)			23～1				23(56)	17(62)	11(68)	5(74)
20×9.0J	53～18	50(59)	44(65)	38(71)	32(77)	26(83)	20(89)		46～11	45(57)	39(63)	33(69)	27(75)	21(81)	15(87)		30～-5			30(56)	24(62)	18(68)	12(74)	6(80)
20×9.5J	53～12	50(65)	44(71)	38(77)	32(83)	26(89)	20(95)	14(101)	50～5	45(63)	39(69)	33(75)	27(81)	21(87)	15(93)	9(99)	36～-12		36(56)	30(62)	24(68)	18(74)	12(80)	6(86)
20×10.0J	53～6	50(72)	44(78)	38(84)	32(90)	26(96)	20(102)	14(108)	50～-1	45(70)	39(76)	33(82)	27(88)	21(94)	15(100)	9(106)	43～-17	42(57)	36(63)	30(69)	24(75)	18(81)	12(87)	6(93)
20×10.5J	53～12	50(78)	44(84)	38(90)	32(96)	26(102)	20(108)	14(114)	50～5	45(76)	39(82)	33(88)	27(94)	21(100)	15(106)	9(112)	43～-11	42(63)	36(69)	30(75)	24(81)	18(87)	12(93)	6(99)
20×11.0J	53～12	50(84)	44(90)	38(96)	32(102)	26(108)	20(114)	14(120)	50～5	45(82)	39(88)	33(94)	27(100)	21(106)	15(112)	9(118)	43～-12	42(69)	36(75)	30(81)	24(87)	18(93)	12(99)	6(105)

* There is no protrusion of the top surface of the disk from the edge of the rim flange on all sizes.

■DISK FINISH：HYPER METAL BLACK, SAMURAI GOLD, GLAZE BLACK

■COMPONENT PARTS: CENTER CAP (2 colors for Hi type and 6 colors for Lo type are available), AIR VALVE

*As of November 30, 2023, the long adapter is no longer included.

■RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

※SAME PRICES ON YOUR CUSTOM ORDER.

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)												
	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi										
21 Normal	--	--	--	--	φ66.5	705KG	φ30	φ14.5	φ73	690KG	φ30	φ14.5	φ72.5	815KG	φ30	φ14.5	32	39	55										
20 Reverse	--	--	--	--																									
20 Normal	φ65	540KG	φ30	φ14.5		700KG																							
19 Reverse																													
19 Normal																													
18 Reverse																													

■MAVERICK1613M is compatible with VIA815KG (5H-120). It can be installed on all grades of Alphard/Vellfire (40 series) and Lexus LM (H10 series).

MAVERICK 1613M **19inch** REVERSE RIM

[2pieces]

Size	S-Lo Disk 5H-114.3							Lo Disk 5H-100 5H-112 5H-114.3 5H-120							Hi Disk 5H-114.3						
	Order Inset	Inset (Rim Depth) mm						Order Inset	Inset (Rim Depth) mm						Order Inset	Inset (Rim Depth) mm					
19×7.5J	50〜42		47(43)	42(48)				43〜35		42(41)	36(47)				27〜19				27(40)	21(46)	
19×8.0J	55〜37	53(44)	47(50)	41(56)				50〜30	48(42)	42(48)	36(54)	30(60)			34〜14			33(41)	27(47)	21(53)	15(59)
19×8.5J	55〜30	53(50)	47(56)	41(62)	35(68)			50〜23	48(48)	42(54)	36(60)	30(66)	24(72)		40〜7		39(41)	33(47)	27(53)	21(59)	15(65)
19×9.0J	55〜22	53(56)	47(62)	41(68)	35(74)	29(80)	23(86)	50〜15	48(54)	42(60)	36(66)	30(72)	24(78)	18(84)	46〜-1	45(41)	39(47)	33(53)	27(59)	21(65)	15(71)
19×9.5J	55〜22	53(63)	47(69)	41(75)	35(81)	29(87)	23(93)	50〜15	48(61)	42(67)	36(73)	30(79)	24(85)	18(91)	46〜-1	45(48)	39(54)	33(60)	27(66)	21(72)	15(78)
19×10.0J	55〜28	53(69)	47(75)	41(81)	35(87)	29(93)		50〜21	48(67)	42(73)	36(79)	30(85)	24(91)		46〜5	45(54)	39(60)	33(66)	27(72)	21(78)	15(84)
19×10.5J	55〜24	53(75)	47(81)	41(87)	35(93)	29(99)		50〜17	48(73)	42(79)	36(85)	30(91)	24(97)	18(103)	46〜1	45(60)	39(66)	33(72)	27(78)	21(84)	15(90)

* There is no protrusion of the top surface of the disk from the edge of the rim flange on all sizes.

- DISK FINISH: HYPER METAL BLACK, SAMURAI GOLD, GLAZE
BLACK
- COMPONENT PARTS: CENTER CAP (2 colors for Hi type and 6 colors for Lo type are available), AIR VALVE
- *As of November 30, 2023, the long adapter is no longer included.
- RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.
- ※SAME PRICES ON YOUR CUSTOM ORDER.

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)		
	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi
21 Normal	--	--	--	--	φ66.5	705KG	φ30	φ14.5	φ73	690KG	φ30	φ14.5	φ72.5	815KG	φ30	φ14.5	32	39	55
20 Reverse	--	--	--	--															
20 Normal	φ65	540KG	φ30	φ14.5		700KG													
19 Reverse																			
19 Normal													--	--	--	--			
18 Reverse													--	--	--	--			

■MAVERICK1613M is compatible with VIA815KG (5H-120). It can be installed on all grades of Alphard/Vellfire (40 series) and Lexus LM (H10 series).

MAVERICK 1613M **19inch** NORMAL RIM

[2pieces]

Size	S-Lo Disk 5H-114.3							Lo Disk 5H-100 5H-112 5H-114.3 5H-120						
	Order Inset	Inset (Rim Depth) mm						Order Inset	Inset (Rim Depth) mm					
19×8.0J	41〜23			38(58)	32(64)	26(70)		34〜16			33(56)	27(62)	21(68)	
19×8.5J	47〜16		44(58)	38(64)	32(70)	26(76)		40〜9		39(56)	33(62)	27(68)	21(74)	15(80)
19×9.0J	53〜23	50(59)	44(65)	38(71)	32(77)	26(83)		46〜16	45(57)	39(63)	33(69)	27(75)	21(81)	
19×9.5J	53〜17	50(65)	44(71)	38(77)	32(83)	26(89)	20(95)	50〜10	45(63)	39(69)	33(75)	27(81)	21(87)	15(93)
19×10.0J	53〜24	50(72)	44(78)	38(84)	32(90)	26(96)		50〜17	45(70)	39(76)	33(82)	27(88)	21(94)	
19×10.5J	53〜23	50(78)	44(84)	38(90)	32(96)	26(102)		50〜16	45(76)	39(82)	33(88)	27(94)	21(100)	

* There is no protrusion of the top surface of the disk from the edge of the rim flange on all sizes.

■DISK FINISH: HYPER METAL BLACK, SAMURAI GOLD, GLAZE
BLACK

■COMPONENT PARTS: CENTER CAP (2 colors for Hi type and 6 colors for Lo type are available), AIR VALVE

*As of November 30, 2023, the long adapter is no longer included.

■RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

✂SAME PRICES ON YOUR CUSTOM ORDER.

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)			
	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi	
21 Normal	--	--	--	--	φ66.5	705KG	φ30	φ14.5	φ73	690KG	φ30	φ14.5	φ72.5	815KG	φ30	φ14.5	32	39	55	
20 Reverse	--	--	--	--																
20 Normal	φ65	540KG	φ30	φ14.5																
19 Reverse																				
19 Normal						700KG							--	--	--	--				
18 Reverse														--	--	--				--

■MAVERICK1613M is compatible with VIA815KG (5H-120). It can be installed on all grades of Alphard/Vellfire (40 series) and Lexus LM (H10 series).

MAVERICK 1613M **18inch** REVERSE RIM

[2pieces]

Size	S-Lo Disk 5H-114.3							Lo Disk 5H-100 5H-112 5H-114.3						
	Order Inset	Inset (Rim Depth) mm						Order Inset	Inset (Rim Depth) mm					
18×7.5J	50〜34		47(43)	41(49)	35(55)			43〜27		42(41)	36(47)	30(53)		
18×8.0J	55〜29	53(44)	47(50)	41(56)	35(62)	29(68)		50〜22	48(42)	42(48)	36(54)	30(60)	24(66)	
18×8.5J	55〜22	53(50)	47(56)	41(62)	35(68)	29(74)	23(80)	50〜15	48(48)	42(54)	36(60)	30(66)	24(72)	18(78)
18×9.0J	55〜22	53(56)	47(62)	41(68)	35(74)	29(80)	23(86)	50〜15	48(54)	42(60)	36(66)	30(72)	24(78)	18(84)
18×9.5J	55〜22	53(63)	47(69)	41(75)	35(81)	29(87)	23(93)	50〜15	48(61)	42(67)	36(73)	30(79)	24(85)	18(91)
18×10.0J	55〜28	53(69)	47(75)	41(81)	35(87)	29(93)		50〜21	48(67)	42(73)	36(79)	30(85)	24(91)	

* There is no protrusion of the top surface of the disk from the edge of the rim flange on all sizes.

- DISK FINISH: HYPER METAL BLACK, SAMURAI GOLD, GLAZE BLACK
- COMPONENT PARTS: CENTER CAP (2 colors for Hi type and 6 colors for Lo type are available), AIR VALVE
- *As of November 30, 2023, the long adapter is no longer included.
- RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.
- ✂SAME PRICES ON YOUR CUSTOM ORDER.

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)																
	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi														
21 Normal	--	--	--	--	φ66.5	705KG	φ30	φ14.5	φ73	690KG	φ30	φ14.5	φ72.5	815KG	φ30	φ14.5	32	39	55														
20 Reverse	--	--	--	--																													
20 Normal	φ65	540KG	φ30	φ14.5		700KG																											
19 Reverse																																	
19 Normal						--							--	--	--																		
18 Reverse						--							--	--	--																		

■MAVERICK1613M is compatible with VIA815KG (5H-120). It can be installed on all grades of Alphard/Vellfire (40 series) and Lexus LM (H10 series).