

905S WHEEL SPEC

MAVERICK 905S **18inch** REVERSE RIM [2pieces]

Size	S-Lo Disk 5H-114.3								Lo Disk 5H-100 5H-114.3								
	Order Inset	Inset (Rim Depth) mm							Order Inset	Inset (Rim Depth) mm							
18x7.5J	49 ~ 31		49 (35)	44 (40)	38 (46)	32 (52)			41 ~ 23			41 (34)	36 (39)	30 (45)	24 (51)		
18x8.0J	55 ~ 25	55 (35)	50 (40)	44 (46)	38 (52)	32 (58)	26 (64)		47 ~ 17		47 (34)	42 (39)	36 (45)	30 (51)	24 (57)	18 (63)	
18x8.5J	56 ~ 18	56 (40)	50 (46)	44 (52)	38 (58)	32 (64)	26 (70)	20 (76)	53 ~ 10	53 (34)	48 (39)	42 (45)	36 (51)	30 (57)	24 (63)	18 (69)	12 (75)
18x9.0J	56 ~ 19	56 (47)	50 (53)	44 (59)	38 (65)	32 (71)	26 (77)	20 (83)	54 ~ 11	54 (40)	48 (46)	42 (52)	36 (58)	30 (64)	24 (70)	18 (76)	12 (82)
18x9.5J	56 ~ 18	56 (53)	50 (59)	44 (65)	38 (71)	32 (77)	26 (83)	20 (89)	54 ~ 10	54 (46)	48 (52)	42 (58)	36 (64)	30 (70)	24 (76)	18 (82)	12 (88)
18x10.0J	56 ~ 25	56 (60)	50 (66)	44 (72)	38 (78)	32 (84)	26 (90)		54 ~ 17	54 (53)	48 (59)	42 (65)	36 (71)	30 (77)	24 (83)	18 (89)	

WARNING: THE HIGHEST SURFACE POINT OF CENTER DISK COMBINED WITH OUTER RIM DEPTH OF UNDER 40mm WILL BE BEYOND OUTER RIM FLANGE. (OUTER RIM DEPTH OF 34mm = 7mm BEYOND)

- DISK FINISH: PREMIUM SILVER, GUN-METAL/POLISH, BLACK/POLISH, MATTE BLACK
- COMPONENT PARTS: CENTER CAP (2 colors for Hi type and 6 colors for Lo type are available) & METAL VALVE STEM
- *As of November 30, 2023, the long adapter is no longer included.
- RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.
- ※SAME PRICES ON YOUR CUSTOM ORDER.

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)		
	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi
18 Reverse	φ65	540KG	φ28.5	φ15	--	--	--	--	φ73	690KG	φ30	φ13	--	--	--	--	26	35	--
19 Reverse					φ66.5	700KG	φ28.5	φ15					--	--	--	48			
20 Normal					--	--	--	--					--	--	--				
20 Reverse	--	--	--	--	φ66.5	705KG	φ28.5	φ15					φ72.5	690KG	φ28.5				φ15
21 Normal	--	--	--	--															

MAVERICK 905S **19inch** REVERSE RIM

[2pieces]

Size	S-Lo Disk 5H-114.3								Lo Disk 5H-100 5H-112 5H-114.3								Hi Disk 5H-114.3										
	Order Inset	Inset (Rim Depth) mm							Order Inset	Inset (Rim Depth) mm							Order Inset				Inset (Rim Depth) mm						
19x7.5J	49 ~ 39		49 (35)	44 (40)	39 (45)				41 ~ 31			41 (34)	36 (39)	30 (45)				28 ~ 18				28 (34)	22 (40)	18 (44)			
19x8.0J	55 ~ 33	55 (35)	50 (40)	44 (46)	38 (52)	33 (57)			47 ~ 25		47 (34)	42 (39)	36 (45)	30 (51)	25 (56)			34 ~ 12			33 (35)	28 (40)	22 (46)	16 (52)	12 (56)		
19x8.5J	56 ~ 26	56 (41)	50 (47)	44 (53)	38 (59)	32 (65)	26 (71)		53 ~ 18	53 (35)	48 (40)	42 (46)	36 (52)	30 (58)	24 (64)	18 (70)		40 ~ 5		40 (35)	34 (41)	28 (47)	22 (53)	16 (59)	10 (65)	5 (69)	
19x9.0J	56 ~ 19	56 (47)	50 (53)	44 (59)	38 (65)	32 (71)	26 (77)	20 (83)	54 ~ 11	54 (40)	48 (46)	42 (52)	36 (58)	30 (64)	24 (70)	18 (76)	12 (82)	46 ~ -2	46 (35)	40 (41)	34 (47)	28 (53)	22 (59)	16 (65)	10 (71)	4 (77)	-2 (83)
19x9.5J	56 ~ 18	56 (54)	50 (60)	44 (66)	38 (72)	32 (78)	26 (84)	20 (90)	54 ~ 10	54 (47)	48 (53)	42 (59)	36 (65)	30 (71)	24 (77)	18 (83)	12 (89)	46 ~ -3	46 (42)	40 (48)	34 (54)	28 (60)	22 (66)	16 (72)	10 (78)	4 (84)	-2 (90)
19x10.0J	56 ~ 25	56 (60)	50 (66)	44 (72)	38 (78)	32 (84)	26 (90)		54 ~ 17	54 (53)	48 (59)	42 (65)	36 (71)	30 (77)	24 (83)	18 (89)		46 ~ 4	46 (48)	40 (54)	34 (60)	28 (66)	22 (72)	16 (78)	10 (84)	4 (90)	
19x10.5J	56 ~ 21	56 (66)	50 (72)	44 (78)	38 (84)	32 (90)	26 (96)		54 ~ 13	54 (59)	48 (65)	42 (71)	36 (77)	30 (83)	24 (89)	18 (95)	13 (100)	46 ~ 0	46 (54)	40 (60)	34 (66)	28 (72)	22 (78)	16 (84)	10 (90)	4 (96)	

WARNING: THE HIGHEST SURFACE POINT OF CENTER DISK COMBINED WITH OUTER RIM DEPTH OF UNDER 40mm WILL BE BEYOND OUTER RIM FLANGE. (OUTER RIM DEPTH OF 34mm = 7mm BEYOND)

- DISK FINISH: PREMIUM SILVER, GUN-META/POLISH, BLACK/POLISH, MATTE BLACK
- COMPONENT PARTS: CENTER CAP (2 colors for Hi type and 6 colors for Lo type are available) & METAL VALVE STEM
- *As of November 30, 2023, the long adapter is no longer included.
- RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.
- ※SAME PRICES ON YOUR CUSTOM ORDER.

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)		
	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi
18 Reverse	φ65	540KG	φ28.5	φ15	--	--	--	--	φ73	690KG	φ30	φ13	--	--	--	--	26	35	48
19 Reverse					φ66.5	700KG	φ28.5	φ15					--	--	--	--			
20 Normal					--	--	--	--					--	--	--	--			
20 Reverse					--	--	--	--					φ66.5	705KG	φ28.5	φ15			
21 Normal	--	--	--	--															

MAVERICK 905S

20inch

NORMAL RIM

[2pieces]

Size	S-Lo Disk 5H-114.3										Lo Disk 5H-100 5H-114.3										Hi Disk 5H-114.3											
	Order Inset	Inset (Rim Depth) mm										Order Inset	Inset (Rim Depth) mm										Order Inset	Inset (Rim Depth) mm								
20x8.5J	39 ~ 21			39 (58)	35 (62)	29 (68)	23 (74)				31 ~ 13				31 (57)	27 (61)	21 (67)	15 (73)			18 ~ 0					18 (57)	13 (62)	7 (68)	1 (74)			
20x9.0J	46 ~ 15		46 (58)	41 (63)	35 (69)	29 (75)	23 (81)	17 (97)			38 ~ 7			38 (57)	33 (62)	27 (68)	21 (74)	15 (80)	9 (86)		25 ~ -6				25 (57)	19 (63)	13 (69)	7 (75)	1 (81)	-5 (87)		
20x9.5J	52 ~ 9	52 (58)	47 (63)	41 (69)	35 (75)	29 (81)	23 (87)	17 (93)	11 (99)		44 ~ 1		44 (57)	39 (62)	33 (68)	27 (74)	21 (80)	15 (86)	9 (92)	3 (98)	31 ~ -13			31 (57)	25 (63)	19 (69)	13 (75)	7 (81)	1 (87)	-5 (93)	-11 (99)	
20x10.0J	53 ~ 3	53 (63)	47 (69)	41 (75)	35 (81)	29 (87)	23 (93)	17 (99)	11 (105)	5 (111)	51 ~ -5	51 (56)	45 (62)	39 (68)	33 (74)	27 (80)	21 (86)	15 (92)	9 (98)	3 (104)	38 ~ -18		37 (57)	31 (63)	25 (69)	19 (75)	13 (81)	7 (87)	1 (93)	-5 (99)	-11 (105)	-17 (111)
20x10.5J	53 ~ 9	53 (70)	47 (76)	41 (82)	35 (88)	29 (94)	23 (100)	17 (106)	11 (112)		51 ~ 1	51 (63)	45 (69)	39 (75)	33 (81)	27 (87)	21 (93)	15 (99)	9 (105)	3 (111)	44 ~ -12	43 (58)	37 (64)	31 (70)	25 (76)	19 (82)	13 (88)	7 (94)	1 (100)	-5 (106)	-11 (112)	
20x11.0J	53 ~ 9	53 (76)	47 (82)	41 (88)	35 (94)	29 (100)	23 (106)	17 (112)	11 (118)		51 ~ 1	51 (69)	45 (75)	39 (81)	33 (87)	27 (93)	21 (99)	15 (105)	9 (111)	3 (117)	44 ~ -13	43 (64)	37 (70)	31 (76)	25 (82)	19 (88)	13 (94)	7 (100)	1 (106)	-5 (112)	-11 (118)	

WARNING: THE HIGHEST SURFACE POINT OF CENTER DISK COMBINED WITH OUTER RIM DEPTH OF UNDER 40mm WILL BE BEYOND OUTER RIM FLANGE. (OUTER RIM DEPTH OF 34mm = 7mm BEYOND)

- DISK FINISH: PREMIUM SILVER, GUN-META/POLISH, BLACK/POLISH, MATTE BLACK
- COMPONENT PARTS: CENTER CAP (2 colors for Hi type and 6 colors for Lo type are available) & METAL VALVE STEM

*As of November 30, 2023, the long adapter is no longer included.

■RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

※SAME PRICES ON YOUR CUSTOM ORDER.

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)					
	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi			
18 Reverse	φ65	540KG	φ28.5	φ15	--	--	--	--	φ73	690KG	φ30	φ13	--	--	--	--	26	35	--			
19 Reverse					φ66.5	700KG	φ28.5	φ15					--	--	--	--						
20 Normal					--	--	--	--					--	--	--	--						
20 Reverse					--	--	--	--					φ66.5	705KG	φ28.5	φ15			φ72.5	690KG	φ28.5	φ15
21 Normal					--	--	--	--														

MAVERICK 905S

20inch

REVERSE RIM

[2pieces]

Size	S-Lo Disk 5H-114.3								Lo Disk 5H-112 5H-114.3 5H-120								Hi Disk 5H-112 5H-114.3 5H-120										
	Order Inset	Inset (Rim Depth) mm							Order Inset	Inset (Rim Depth) mm							Order Inset	Inset (Rim Depth) mm									
20x8.0J	56 ~ 34	56 (34)	50 (40)	44 (46)	38 (52)	34 (56)			47 ~ 25		47 (34)	42 (39)	36 (45)	30 (51)	25 (56)			34 ~ 12			33 (35)	28 (40)	22 (46)	16 (52)	12 (56)		
20x8.5J	56 ~ 27	56 (41)	50 (47)	44 (53)	38 (59)	32 (65)	27 (70)		53 ~ 18	53 (35)	48 (40)	42 (46)	36 (52)	30 (58)	24 (64)	18 (70)		40 ~ 5		40 (35)	34 (41)	28 (47)	22 (53)	16 (59)	10 (65)	5 (69)	
20x9.0J	56 ~ 20	56 (47)	50 (53)	44 (59)	38 (65)	32 (71)	26 (77)	20 (83)	54 ~ 11	54 (40)	48 (46)	42 (52)	36 (58)	30 (64)	24 (70)	18 (76)	12 (82)	46 ~ -2	46 (35)	40 (41)	34 (47)	28 (53)	22 (59)	16 (65)	10 (71)	4 (77)	-2 (83)
20x9.5J	56 ~ 19	56 (54)	50 (60)	44 (66)	38 (72)	32 (78)	26 (84)	20 (90)	54 ~ 10	54 (47)	48 (53)	42 (59)	36 (65)	30 (71)	24 (77)	18 (83)	12 (89)	46 ~ -3	46 (42)	40 (48)	34 (54)	28 (60)	22 (66)	16 (72)	10 (78)	4 (84)	-2 (90)
20x10.0J	56 ~ 26	56 (60)	50 (66)	44 (72)	38 (78)	32 (84)	26 (90)		54 ~ 17	54 (53)	48 (59)	42 (65)	36 (71)	30 (77)	24 (83)	18 (89)		46 ~ 4	46 (48)	40 (54)	34 (60)	28 (66)	22 (72)	16 (78)	10 (84)	4 (90)	
20x10.5J	56 ~ 22	56 (66)	50 (72)	44 (78)	38 (84)	32 (90)	26 (96)		54 ~ 13	54 (59)	48 (65)	42 (71)	36 (77)	30 (83)	24 (89)	18 (95)	13 (100)	46 ~ 0	46 (54)	40 (60)	34 (66)	28 (72)	22 (78)	16 (84)	10 (90)	4 (96)	

WARNING: THE HIGHEST SURFACE POINT OF CENTER DISK COMBINED WITH OUTER RIM DEPTH OF UNDER 40mm WILL BE BEYOND OUTER RIM FLANGE. (OUTER RIM DEPTH OF 34mm = 7mm BEYOND)

- DISK FINISH: PREMIUM SILVER, GUN-META/POLISH, BLACK/POLISH, MATTE BLACK
- COMPONENT PARTS: CENTER CAP (2 colors for Hi type and 6 colors for Lo type are available) & METAL VALVE STEM
- *As of November 30, 2023, the long adapter is no longer included.
- RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.
- ※SAME PRICES ON YOUR CUSTOM ORDER.

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)								
	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi						
18 Reverse	φ65	540KG	φ28.5	φ15	--	--	--	--	φ73	690KG	φ30	φ13	--	--	--	--	26	35	--						
19 Reverse					φ66.5	700KG	φ28.5	φ15					--	--	--	--									
20 Normal					--	--	--	--					--	--	--	--									
20 Reverse					--	--	--	--					φ66.5	705KG	φ28.5	φ15			φ72.5	690KG	φ28.5	φ15			
21 Normal					--	--	--	--																	

MAVERICK 905S **21inch** NORMAL RIM

[2pieces]

Size	S-Lo Disk 5H-114.3								Lo Disk 5H-112 5H-114.3 5H-120								Hi Disk 5H-112 5H-114.3 5H-120										
	Order Inset	Inset (Rim Depth) mm							Order Inset	Inset (Rim Depth) mm							Order Inset	Inset (Rim Depth) mm									
21x9.0J	49 ~ 23		47 (57)	41 (63)	35 (69)	29 (75)	23 (81)		40 ~ 14			39 (56)	33 (62)	27 (68)	21 (74)	15 (80)		27 ~ 1				25 (57)	19 (63)	13 (69)	7 (75)	1 (81)	
21x9.5J	55 ~ 16	53 (57)	47 (63)	41 (69)	35 (75)	29 (81)	23 (87)	17 (93)	46 ~ 7		45 (56)	39 (62)	33 (68)	27 (74)	21 (80)	15 (86)	9 (92)	33 ~ -7			31 (57)	25 (63)	19 (69)	13 (75)	7 (81)	1 (87)	-5 (93)
21x10.0J	55 ~ 17	53 (63)	47 (69)	41 (75)	35 (81)	29 (87)	23 (93)	17 (99)	53 ~ 8	51 (56)	45 (62)	39 (68)	33 (74)	27 (80)	21 (86)	15 (92)	9 (98)	40 ~ -6		37 (57)	31 (63)	25 (69)	19 (75)	13 (81)	7 (87)	1 (93)	-5 (99)
21x10.5J	55 ~ 23	53 (70)	47 (76)	41 (82)	35 (88)	29 (94)	23 (100)		53 ~ 14	51 (63)	45 (69)	39 (75)	33 (81)	27 (87)	21 (93)	15 (99)		46 ~ 1	43 (58)	37 (64)	31 (70)	25 (76)	19 (82)	13 (88)	7 (94)	1 (100)	
21x11.0J	55 ~ 23	53 (76)	47 (82)	41 (88)	35 (94)	29 (100)	23 (106)		53 ~ 14	51 (69)	45 (75)	39 (81)	33 (87)	27 (93)	21 (99)	15 (105)		46 ~ 1	43 (64)	37 (70)	31 (76)	25 (82)	19 (88)	13 (94)	7 (100)	1 (106)	

WARNING: THE HIGHEST SURFACE POINT OF CENTER DISK COMBINED WITH OUTER RIM DEPTH OF UNDER 40mm WILL BE BEYOND OUTER RIM FLANGE. (OUTER RIM DEPTH OF 34mm = 7mm BEYOND)

- DISK FINISH: PREMIUM SILVER, GUN-META/POLISH, BLACK/POLISH, MATTE BLACK
- COMPONENT PARTS: CENTER CAP (2 colors for Hi type and 6 colors for Lo type are available) & METAL VALVE STEM
- *As of November 30, 2023, the long adapter is no longer included.
- RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.
- ※SAME PRICES ON YOUR CUSTOM ORDER.

Size	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)		
	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi
18 Reverse	φ65	540KG	φ28.5	φ15	--	--	--	--	φ73	690KG	φ30	φ13	--	--	--	--	26	35	48
19 Reverse					φ66.5	700KG	φ28.5	φ15					--	--	--	--			
20 Normal					--	--	--	--					--	--	--	--			
20 Reverse					--	--	--	--					φ66.5	705KG	φ28.5	φ15			
21 Normal	--	--	--	--															